

HPL SERIES



High Repetition Rate / High Power
Picosecond Pulsed Diode Lasers



The HPL high repetition rate / high power picosecond pulsed diode lasers are a series of pulsed sources designed for Time-Correlated Single Photon Counting (TCSPC) measurements with repetition rates up to 80 MHz.

When operating in standard pulse mode, HPL lasers provide pulses of <math><150\text{ ps}</math> making them the ideal source for measuring short fluorescence lifetimes.

For experiments that require higher excitation energy, the high-power operation mode may be enabled. This mode offers average powers of a few mW whilst maintaining sub-nanosecond pulse widths.

HPL lasers are designed with Edinburgh Instruments spectrometers in mind and are directly mounted onto their standard laser couplings, but they are fully independent and do not need an external controller. This, together with their external trigger capability, makes them easily integrated into any experiment.

KEY FEATURES

- + Repetition rates from 1 kHz up to 80 MHz
- + Standard and high-power operation mode
- + External trigger capability
- + Spectrally purified output
- + Compact plug-and-play design
- + Extremely low RF radiation
- + Optimised collimated beam
- + Embedded drive electronics



SPECIFICATIONS

Model (HPL-)	405	420	445	450	475	485	510	635	655	670	785	800
Nominal Wavelength (± 10 nm)	405	420	445	450	475	485	510	635	655	670	785	800
Linewidth (nm)	2.0 \pm 0.5	3.0 \pm 1.0	3.0 \pm 1.0	7.0 \pm 1.0	4.5 \pm 1.0	7.0 \pm 4.0	5.0 \pm 0.5	2.5 \pm 0.5	2.5 \pm 0.5	2.5 \pm 0.5	4.0 \pm 3.0	6.0 \pm 3.0
Maximum Repetition Rate (MHz)	80	80	80	80	80	80	80	80	80	80	80	80
Typical Pulse Width (ps) *	80	120	95	105	100	144	165	95	85	65	100	146
Typical Standard Average Power (mW) **	0.45	0.76	0.30	0.92	0.50	0.37	1.20	0.50	0.50	0.65	0.30	4.30
Typical High Average Power (mW) **	4.55	5.30	0.75	6.70	2.0	2.30	4.00	2.20	5.40	1.50	5.00	13.5
Typical Standard Peak Power (mW) **	70	215	100	110	100	30	110	90	55	130	35	300

* In standard power mode.

** Measured at maximum repetition rate. Power may be increased by a factor of 1.1 – 4 (wavelength dependent) by removing the cleanup filter on the laser.

REPETITION RATE

MHz: 80[†], 40, 20, 10, 5, 2
kHz: 1000, 500, 200, 100, 50, 20, 10, 5, 2.5, 1[†]
[†]Wavelength dependent

BIAS SUPPLY

15 Vdc +/- 5%, 15W (2.1mm DC jack)

TRIGGER OUTPUT

SMA, NIM Standard

INTERLOCK INPUT

Hirose HR10A-7P-4P(73), (Link pin 1 and pin 2 to ground – interlock healthy)

TRIGGER INPUT

Hirose HR10A-7P-4P(73), (Signal pin 4 and ground pin 3)

TRIGGER INPUT SIGNAL

TTL > 50 ns pulse. Trigger on rising edge.
0.0 V < Low level < 0.5 V, 2.5 V < High level < 5 V

KEY SWITCH

Yes

BEAM QUALITY

10% - 90% Knife Edge Method
Beam diameter < 9.5 mm at HPL output aperture
Beam diameter < 25 mm after 250 mm propagation

SPECTRAL CONDITIONING

Built-in filter to minimise out-of-band emission (no external spectral filtering needed)

PHYSICAL DIMENSIONS

Overall: 168 mm length x 64 mm x 64 mm
Collimator tube: \varnothing 30 mm x 38 mm

TAPPED HOLES FOR STUD MOUNT

2 x M6


WEIGHT

750 g

Other wavelengths available upon request.

CLASS 3B LASER PRODUCT

Avoid exposure to beam. Light emitted by the source may be harmful to the human eye and to skin. Please obey laser safety regulations.
This product complies with the US federal laser product performance standards.



Customer support is available worldwide.

edinst.com

Registered in England and Wales No: 962331 VAT No:GB 271 7379 37

All specifications are correct at the time of production. We reserve the right to change our specifications without notice.

©Edinburgh Instruments Ltd. 2024

STG06 / 12.24



超高真空・極低温走査型プローブ顕微鏡
高速分光測定装置、クライオスタット



Nd:YAGレーザー、Ti:Sレーザー
OPOLレーザー

- 本カタログに記載されている内容は、改良のため予告無く変更する場合があります。（製品の仕様、性能、価格などはカタログ発行当時のものです）
- 本カタログに記載されている内容の一部または全部を無断で転載することは禁止されております。
- 本カタログに記載されているメーカー名、製品名などは各社の商標または登録商標です。